MACHEREY-NAGEI



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058	NANOCOLOR Manganese 10	Page: 1/11
Printing date: 01.10.2019	Date of issue: 13.08.2019	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

> REF Product name

985058 NANOCOLOR Manganese 10

REACH Registration number(s): see SECTION 3.1/3.2 or A registration number for the substance(s) does not exist because the annual tonnage does not require registration or the substance or its use is excluded from registration.

> 20 x 0.5 mL Manganese 10 (R0) 1 x 11 mL Manganese 10 (R2) 1 x 1.5 g Manganese 10 (R3)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Product for analytical use. Exposure Scenario Classification according REACh, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0 The exposure scenario is integrated into sections 1-16. Uses advised against not described

1.3 Details of the supplier of the safety data sheet

Manufactured by:

MACHEREY-NAGEL GmbH & Co. KG Neumann-Neander-Str. 6-8, 52355 Dueren, GERMANY Tel.: +49 2421 969 0

1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service. DE: Gemeinsames Giftinformationszentrum (GGIZ) 99089 Erfurt tel. +49 361 730 730

You find our current versions of SDS (22 languages) in Internet:

http://www.mn-net.com/SDS

E-mail: sds@mn-net.com (msds@mn-net.com)

SECTION 2: Hazard identification

2.0 Classification of the complete product



Signal word	DANGER
Hazard identification	Hazard classes/categories
H290	Met. Corr. 1
H302	Acute Tox. 4 oral
H312	Acute Tox. 4 derm.
H314	Skin Corr. 1B
H317	Skin Sens. 1
H335	STOT SE 3
H351	Carc. 2
H373	STOT RE 2

2.1 Classification of the substance or mixture

0.5 mL Manganese 10 (R0)

ACHEREY-NAGE

(MN>

ISO 9001 CERTIFIEI

www.mn-net.com

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: US: Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

HEREY-NAGEI



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

GHS07

REF: 985058	NANOCOLOR Manganese 10	Page: 2/1
Printing date: 01.10.2019	Date of issue: 13.08.2019	
Finding date. 01.10.2019	Date of issue. 13.06.2019	

GHS08

Signal word WARNING Hazard identification Hazard classes/categories H290 Met. Corr. 1 H302 Acute Tox. 4 oral Acute Tox. 4 derm. H312 Skin Sens. 1 H317 H351 Carc. 2 H373 STOT RE 2

11 mL Manganese 10 (R2)

	GHS05 GHS07
Signal word	DANGER
Hazard identification	Hazard classes/categories
H314 H335	Skin Corr. 1B STOT SE 3
.5 g Manganese 10 (R3)	

Signal word	WARNING
Hazard identification	Hazard classes/categories
H373	STOT RE 2

GHS08

2.2 Label elements

According CLP directive inner packages must be only labelled with GHS symbol(s) and product identificator(s) (EU 1272/2008 Annex I - 1.5.1.2). Inner packages up to 10 mL need max. 2 symbols (Annex I - 1.5.2.4.1 / 2).

Harmful chemicals/mixtures with signal word: WARNING must not be labelled with H and P phrases until 125 mL (EU 1272/2008 Annex I - 1.5.2). This labelling exemption is NOT valid for sensibilizing substances. Metal corrosive solutions do not have to be labelled with GHS symbol, signal word, H and P phrases until 125 mL (EU 1272/2008 Annex I - 1.5.2.1.3).

0.5 mL Manganese 10 (R0)



Signal word: WARNING

H317, H351 May cause an allergic skin reaction. Suspected of causing cancer.



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: Version: MV 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com

US: +33 388 68 22 68 Tel.: +33 388 51 76 88 Fax: E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

www.mn-net.com

+1 484 821 0984

+1 484 821 1272

CHEREY-NAGE



Safety Data Sheet

according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058 NANOCOLOR Manganese 10 Page: 3/11 Date of issue: 13.08.2019 Printing date: 01.10.2019

P261sh. P280sh

Avoid breathing dust/vapours. Wear protective gloves/eye protection.

11 mL Manganese 10 (R2)



Signal word: DANGER

H314

Causes severe skin burns and eye damage.

P260sh, P280sh, P303+361+353, P305+351+338, P310

Do not breathe dust/vapours. Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

1.5 g Manganese 10 (R3)



Signal word: WARNING

2.3 Other hazards

Possible hazards from physicochemical properties

Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive. In the case of pH values are less than 5 or higher than 9 then it is irritant. --

Information pertaining to particular risks to human and possible symptoms

Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs. Cause after oral intake, inhalation of vapours/dust, skin contact, impairments of health when ingested in small quantities. May

cause sensitization by skin contact, also in repeated contact of small amounts. Suspected of causing cancer.

Information pertaining to particular risks to the environment

Avoid contact of substance/mixture to environment. PBT: not applicable not applicable vPvB:

Other hazards

SECTION 3: Composition/information on ingredients

3.1 Substances or 3.2 Mixtures

0.5 mL Manganese 10 (R0)

1	Manyanese TU (RU)			
	Chemical: parafor	rmaldehyde		CAS No.: 30525-89-4
	Classification:	H228, Flam. Sol. 1, H302, Acute Tox	k. 4 oral, H315, Skin Ir	rit. 2, H317, Skin Sens. 1, H318, Eye
	Dam. 1, H332, Acute	Tox. 4 inh., H335, STOT SE 3, H351	, Carc. 2	-
	Formula:	(CH ₂ O) _n		
	TSCA Inventory:	listed		
	RTECS:	RV0540000	MFCD:	00133991
	Concentration:	1 - <3 %		
	acc. CLP (GHS):	H317, Skin Sens. 1, H351, Carc. 2		

ACHEREY-NAGE MN>

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: US: Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058		COLOR Manganese 10	Page: 4/
Printing date: 01.10.2019	Date o	of issue: 13.08.2019	
Formula Pseudor TSCA In	cation: H290, Met. Corr. 1, ns. 1, H319, Eye Irrit. 2, H351, Ca n: NH ₂ OH•HCl/ H ₄ Cll nym: hydroxylamin hydro nventory: listed	H302, Acute Tox. 4 oral, H312, A rc. 2, H373, STOT RE 2, H400, A NO	CAS No.: 5470-11-1 cute Tox. 4 derm., H315, Skin Irrit. 2, H317, quatic Acute 1
EC No.: RTECS: KE No.: Concent	NC3675000 KE-20602, >1% Toy	Indice No.: MFCD: kic 97-1-411	612-123-00-2 00051089
acc. CLF		H302, Acute Tox. 4 oral, H312, A	cute Tox. 4 derm., H317, Skin Sens. 1, H351
11 mL Manganes	se 10 (R2)		
Chemica Classific Formula Pseudor	al: ammonia solution cation: H314, Skin Corr. 1E n: NH ₃ •H ₂ O nym: ammonium hydroxio	3, H335, STOT SE 3, H400, Aquat de, Aqua ammonia, aqueous amm	
REACH EC No.: RTECS: KE No.: Concent	215-647-6 BQ9625000 KE-01688, >10% To		007-001-01-2 00011418
1.5 g Manganese			
	cation: No criteria for classification: C ₆ H ₈ O ₆ nym: vitamin C nventory: listed Reg. No.: exempt, Annex IV	on or naming of chemical not required.	CAS No.: 50-81-7
RTECS: KE No.: Concent	CI7650000 KE-01947	MFCD:	00064328
Chemica Classific Formula TSCA In EC No.:	cation: H332, Acute Tox. 4 t: C ₁₀ H ₁₄ N ₂ Na ₂ O ₈ • iventory: listed (CAS 139-33-	inh., H373, STOT RE 2 2 H ₂ O	CAS No.: 6381-92-6
RTECS: Concent acc. CLF	AH4410000; AH437 tration: 40 - <50 %	75000 MFCD:	00150037

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%.

List of H and P phrases: see section 16.1

SECTION 4: First aid measures

4.1 **Description of first aid measures**

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor.

4.1.1 After SKIN Contact

Remove contaminated clothing immediately. Rinse the affected skin or mucous membrane thoroughly for min. 15 minutes under running water. (If possible) use soap. Avoid neutralisation. Then apply a loose bandage.



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: +49 24 21 969-0 Tel.: +49 24 21 969-199 Fax:

Version: MV 4.10.1 E-mail: info@mn-net.com

Tel.:

Fax:

+41 62 388 55 00 +41 62 388 55 05 E-mail: sales-ch@mn-net.com FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com www.mn-net.com

US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 9	85058	NANOCOLOR Manganese 10	Page: 5/11
Printing	g date: 01.10.2019	Date of issue: 13.08.2019	
4.1.2	bottle, eye douche or running w	thoroughly under running water with the eyelid wide open for min. 1 ater (protect intact eye). Before (if possible) apply eye drops Proxym Further treatment to be carried out by an eye specialist.	
4.1.3	After INHALATION of vapours After inhalation of foam or vapo recovery position and keep airw	ur fresh air should be inhaled. Keep airways free. If vomiting and if in	sensible place patient in
4.1.4		h activated charcoal supplement should be drunk after it has been ir ot make any efforts to neutralise it. Contact medical advice for possib	
4.2		and effects, both acute and delayed act, also in repeated contact of small amounts. Carcinogenic Effects	: Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

CORROSIVE DAMAGE: After SKIN CONTACT rinse with water for a long time. Efforts to neutralise the substance can frequently make matters worse. Apply glucocorticosteroides following inflammatory reactions. After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must to be carried out by an eye specialist. After INTAKE administer aluminium oxide drug suspensions. Administer a prophylaxis to counter pulmonary oedema following the INGESTION of corrosive aerosols. In the event of RESPIRATORY DISTREES ensure that the patient inhales oxygen. Inform patient respectively further measures and the possibility of long-term damages. ---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

5.2 Special hazards arising from the substance or mixture

Formation of hazardous and caustic vapour-air mixtures possible. ---

5.3 Advice for firefighters

No, for listed product. Product package burns like paper or plastic. Spray any vapours released with water. Retent fire water. Use only acid-resistant safety equipment.

For great amount - if necessary - protective breathing apparatus which is independent of the ambient air (isolated equipment), and sealed protective clothing is necessary in the event of a large-scale formation of toxic substances.

5.4 Additional information

Danger for environment only in the event of a large-scale leakage or formation of hazardous substances. ---

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapours. Wear suitable protective gloves (see 8.2.2). Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.

6.2 Environmental precautions

not necessary

6.3 Methods and material for containment and cleaning up

Bind any escaping liquid with inert absorbent. And dispose in accordance to local regulations for the disposal of hazardous chemicals. Clean any contaminated equipment and floors with plenty of water. Collect small amounts of leaked liquid and flush with water into drains.

6.4 Reference to other sections

see information in section 5.4 ---

see information in section 5.4 ---

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling in accordance with the test instruction, that comes with the product. Use a safety bottle when shaking test tubes.

ISO 9001 CERTIFIED

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: **FR**· Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com

US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

Printing date: 01.10.2019 Date of issue: 13.08.2019 7.2 Conditions for safe storage, including any incompatibilities The original product package of MACHEREY-NAGEL allows a safe storage. Storage class (VCI): 4.1A Water hazard class (DE): 3 7.3 Requirements for stock rooms and containers Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of gla 7.3 Specific end use(s) Product for analytical use. SECTION 8: Exposure controls/personal protection 8.1 Control parameters NIOSH: NIOSH: not listed (TWA) Time-weighted average to a reference period of 8 hours. [STEL] Short-term exposure limit related to a 15-minute period OSHA: NIOSH: not listed (TWA) Time-weighted average to a reference period of 8 hours. [STEL] Short-term exposure limit related to a 15-minute period OSHA: NIOSH: not listed (TWA) Time-weighted average to a reference period of 8 hours. [STEL] Short-term exposure limit related to a 15-minute period OSHA: NIOSH: not listed (TWA) Time-weighted average to a reference period of 8 hours. [STEL] Short-term exposure limit related to a 15-minute period OSHA: NIOSH: not listed (TWA) Time-weighted average to a reference period of 8 hours. [STEL] Short-term exposure limit related	
The original product package of MACHEREY-NAGEL allows a safe storage. Storage class (VCI): 4.1A Water hazard class (DE): 3 7.2.1 Requirements for stock rooms and containers Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of gla 7.3 Specific end use(s) Product for analytical use. SECTION 8: Exposure controls/personal protection 8.1 Control parameters 0.5 mL Manganese 10 (R0) Chemical: paraformaldehyde CAS No.: 30525-89-4 NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed 11 mL Manganese 10 (R2) Chernical: annonia solution DNEL: Derived No-Effect Level (for workers) PNEC(frees water): 0.0011 mg/L PNEC(Frees water): 0.001 mg/L PNEC(Frees water): 0.001 mg/L	
7.2.1 Requirements for stock rooms and containers Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of gla 7.3 Specific end use(s) Product for analytical use. SEECTION 8: Exposure controls/personal protection 8.1 Control parameters 0.5 mL Manganese 10 (R0) Chemical: paraformaldehyde CAS No.: 30525-89-4 NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed Chemical: hydroxylammonium chloride CAS No.: 5470-11-1 TRGS 900 (DE): 1.5 mg/m ³ Ere respirable NIOSH: not listed ITWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed Chemical: hydroxylammonium chloride [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed 11 mL Manganese 10 (R2) Chemical: ammonia solution CAS No.: 1336-21-6 DINEL: DINEL = Derived No-Effect Level (for workers) PNEC = Predicate No Effect Concentration PNEC = Predicate No Effect Concentration CAS No.: 1336-21-6	
Product for analytical use. SECTION 8: Exposure controls/personal protection 3.1 Control parameters 6.5 mL Manganese 10 (R0) CAS No.: 30525-89-4 NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed Chemical: hydroxylammonium chloride CAS No.: 5470-11-1 TRGS 900 (DE): 1.5 mg/m³ E/e respirable NIOSH: not listed NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TwA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TwA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period	ss bottles
S.1 Control parameters O.5 mL Manganese 10 (R0) Chemical: paraformaldehyde TVM3 Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed Chemical: hydroxy/ammonium chloride CAS No.: 5470-11-1 TRGS 900 (DE): 1.5 mg/m ³ E/e respirable NIOSH: not listed TTWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed TTWA Time-weighted Ave-Effect Level (for workers) DNEL = Derived No-Effect Level (for workers) PNEC (fresh water): 0.0011 mg/L PNEC = Predicted No Effected Concentration	
0.5 mL Manganese 10 (R0) CAS No.: 30525-89-4 Chemical: paraformaldehyde CAS No.: 30525-89-4 NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed Chemical: hydroxylammonium chloride CAS No.: 5470-11-1 TRGS 900 (DE): 1.5 mg/m³ E/e respirable NIOSH: not listed NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed DNEL: [Inh] 14 mg/m³ DNEL = Derived No-Effect Level (for workers) PNEC (Ifresh water): 0.0011 mg/L PNEC = Predicted No Effected Concentration <td></td>	
Chemical: paraformaldehyde CAS No.: 30525-89-4 NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed Chemical: hydroxylammonium chloride CAS No.: 5470-11-1 TRGS 900 (DE): 1.5 mg/m³ E/e respirable NIOSH: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TMA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed [TMA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed DNEL: [inh] 14 mg/m³ DNEL = Derived No-Effect Level (for workers) PNEC = Pre	
Chemical: hydroxylammonium chloride CAS No.: 5470-11-1 TRGS 900 (DE): 1.5 mg/m³ E/e respirable NIOSH: not listed It me-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed 11 mL Manganese 10 (R2) CAS No.: 1336-21-6 DNEL: [inh] 14 mg/m³ DNEL = Derived No-Effect Level (for workers) PNEC (fresh water): 0.0011 mg/L PNEC = Predicted No Effected Concentration	
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period OSHA: not listed 11 mL Manganese 10 (R2) Chemical: ammonia solution CAS No.: 1336-21-6 DNEL: [inh] 14 mg/m ³ DNEL = Derived No-Effect Level (for workers) PNEC(fresh water): 0.0011 mg/L PNEC = Predicted No Effected Concentration	
Chemical: ammonia solution CAS No.: 1336-21-6 DNEL: [inh] 14 mg/m ³ DNEL = Derived No-Effect Level (for workers) PNEC(fresh water) : 0.0011 mg/L PNEC = Predicted No Effected Concentration	
PNEC _{(fresh water}): 0.0011 mg/L PNEC = Predicted No Effected Concentration	
ELL value: $20 \text{ npm} / 14 \text{ mg/m}^3$	
TRGS 900 (DE): 20 ppm / 14 mg/m ³ E/e respirable	
Short-term exposure factor: 2 (I), Y skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded	
SUVA(CH) MAK value: 20 ppm / 14 mg/m³ NIOSH: [TWA] 25 ppm / 18 mg/m³ NIOSH STEL: 35 ppm / 27 mg/m³ [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period	
OSHA: Yes (TQ = 15000 lbs) - n/a; [TWA] 50 ppm / 35 mg/m ³	
1.5 g Manganese 10 (R3) CAS No.: 50-81-7	
Chemical: ethylendinitrilo tetraacetic acid, di Na-salt (EDTA-Na) CAS No.: 6381-92-6 DNEL: [inh] 1.5 mg/m³ DNEL = Derived No-Effect Level (for workers) CAS No.: 6381-92-6	
PNEC _(fresh water) : 2.2 mg/L PNEC = Predicted No Effected Concentration	
3.2 Exposure controls Good ventilation and extraction system in the room, floor resistant to chemicals with floor drainage and washing facilities. The	highest
level of cleanliness must be maintained at the workplace.	

8.2.1 **Respiratory protection** No additional recommendations.

8.2.2 Hand protection

Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

Eye protection 8.2.3



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: +41 62 388 55 00 Tel.: +49 24 21 969-0 Tel.: Tel.: +33 388 68 22 68 +49 24 21 969-199 Fax: Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com

US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058	NANOCOLOR Manganese 10	Page: 7/11
Printing date: 01.10.2019	Date of issue: 13.08.2019	

Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.

8.2.4 Skin protection

Recommended to avoid clothing damage, and to avoid contamination with these hazards.

Colour: colourless

Colour: colourless

9-10.5

0,98 g/cm³

0-100 %

8.2.5 Personal hygiene

Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.

Odor: penetrative

Odor: aminic

Odor: odorless

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

0.5 mL Manganese 10 (R0) Appearance: liquid

11 mL Manganese 10 (R2) Appearance: liquid pH: Specific gravity: Solubility in water:

1.5 g Manganese 10 (R3)	
Appearance: solid	Colour: white
pH:	5-7
Solubility in water:	0-30 %

9.2 Other information

Data for the other parameters of the mixtures are not available, because no registration and no chemical safety report is required. **Relevant Properties of Substance Group**

SECTION 10: Stability and reactivity

10.1 Reactivity

Strong CORROSIVE, no further data available.

- 10.2 **Chemical stability**
- No known instability. 10.3 Possibility of hazardous reactions

Can react violently with organic material. No further data available.

10.4 Conditions to avoid

Not necessary. Observe labeled storage temperature. ---

10.5 Incompatible materials Avoid contact with strong acids or alkalines.

10.6 Hazardous decomposition products In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Following information is valid for pure substances. Quantitative data on the toxicity of this product are not available.

0.5 mL Manganese 10 (R0)

- (-)	
paraformaldehyde	CAS No.: 30525-89-4
listed	California Proposition 65 List: not listed
not listed	Canada CEPA 1999: DSL Yes
not listed, Japan	PDSCL: not listed
Article 57-2 (SDS	S required)
not listed	
592 mg/kg	
	listed not listed not listed, Japan Article 57-2 (SDS not listed

MACHEREY-NAGE $\langle MN \rangle$ ISO 9001 CERTIFIEI

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: US: Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058	NANOCOLOR Manganese 10	Page: 8/11
Printing date: 01.10.2019	Date of issue: 13.08.2019	

Acute Effects: Cause after skin contact, impairments of health when ingested in small quantities. May cause sensitization by skin contact, also in repeated contact of small amounts. Carcinogenic Effects: Suspected of causing cancer.

Chemical: hydroxylammonium chloride CAS No.: 5470-11-1 TSCA Inventory: California Proposition 65 List: not listed listed Exposure Routes: _ Symptoms: _ Australia NICNAS: not listed Canada CEPA 1999: DSL Yes Japan CSCL/PRTR: not listed, Japan PDSCL: Deleterious Substance Japan ISHL: not listed South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-20602, >1% Toxic 97-1-411 LD50orl rat : 141 mg/kg Acute Effects: Cause after oral intake, inhalation of vapours/dust, skin contact, impairments of health when ingested in small quantities. Chronic Effects: May cause sensitization by skin contact, also in repeated contact of small amounts. May cause damage to organs through prolonged or repeated exposure. Carcinogenic Effects: Suspected of causing cancer. TRGS 907 (DE): Sh

11 mL Manganese 10 (R2)

•	\ /	
Chemical:	ammonia solution	CAS No.: 1336-21-6
TSCA Inventory:	listed	California Proposition 65 List: not listed
Exposure Routes:	inhalation, ingest	ion (solution), skin and/or eye contact (solution/liquid)
Target Organs:	Eyes, skin, respir	atory system
Symptoms:	irritation eyes, no	se, throat; dyspnea (breathing difficulty), wheezing, chest pain; pulmonary edema;
pink frothy sputum; sk	in burns, vesiculation; I	
Australia NICNAS:	not listed	Canada CEPA 1999: DSL yes, Toxic Substances (Schedule 1) Yes
(Item 53.)		
Japan CSCL/PRTR:		PDSCL: Deleterious Substance
Japan ISHL:	listed ≥0,2%/≥0,1	%, Article 57-2 (SDS required)
South Korea TCCA:	not listed	
	entory: KE-01688, >10%	Toxic 97-1-184
LD50 _{orl rat} :	350 mg/kg	
LC_Low _{ihl hmn} :	5000 mg/m³	
LC50ihl rat :	[4h] 2000 ppm	
LD50 _{drm rbt} :	[5min] 5000 ppm	
Acute Effects: Cause	after inhalation of vapour	s/dust, impairments of health when ingested in small quantities.

1.5 g Manganese 10 (R3)

Chemical: TSCA Inventory: Korea Exist.Chem.I	L(+)-ascorbic acid listed nventory: KE-01947	CAS No.: 50-81-7
LD50 _{orl rat} :	11900 mg/kg	
LD50 _{ivn mus} :	518 mg/kg	
Chemical: TSCA Inventory: LD50 _{orl rat} :	ethylendinitrilo tetraacetic acid, di Na-salt (EDTA-Na) listed (CAS 139-33-3) 2800 mg/kg	CAS No.: 6381-92-6

Chronic Effects: May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1 Toxicity

Following information is valid for pure substances.

0.5 mL Manganese 10 (R0)

Chemical:	paraformaldehyd	е
Water hazard clas	s (DE): 2	
Storage class (VC): 11	I

CAS No.: 30525-89-4

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com

US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058	NANOCOLOR Manganese 10	Page: 9/1
Printing date: 01.10.2019	Date of issue: 13.08.2019	
Chemical: hydroxylan LC50 _{leuciscus} idus/96h : Water hazard class (DE): Storage class (VCI):	nmonium chloride 1-10 mg/L 3 4.1 A	CAS No.: 5470-11-1
11 mL Manganese 10 (R2) Chemical: ammonia s Avoid contact of substance/mixtu PNEC(fresh water) : PNEC = Predicted No Effected Concentr LC50fish/96h : EC50daphnia/48h : Water hazard class (DE): Storage class (VCI):	ure to environment.	CAS No.: 1336-21-6
1.5 g Manganese 10 (R3) Chemical: <i>L(+)-ascorr</i> Water hazard class (DE): Storage class (VCI):	bic acid 1 WGK No.: 0737 13	CAS No.: 50-81-7
Chemical: ethylendini PNEC (fresh water) : PNEC = Predicted No Effected Concentr LC50fish/96h : EC50daphnia/48h : IC50scenedesmus quadricauda/72h : EC10pseudomonas putita/16h : Water hazard class (DE): Dispersion coefficient(octanol-wate Storage class (VCI):	[4d] 41-1592 mg/L 140 mg/L [72h] 2.77-1000 mg/L [EC10, 30h] 500 mg/L 2	CAS No.: 6381-92-6
2.2 Persistence and degradability not necessary		
2.3 Bioaccumulative potential not necessary		
2.4 Mobility in soil not necessary		

12.5 Results of PBT and vPvB assessment no data available

12.6 Other adverse effects

no additional data available

SECTION 13: Disposal considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

13.1 Waste treatment methods

SECTION 14: Transport information

	UN number: Class:			UN proper shipping Packing group: II	name: Chemical Kit
Road	transport				
Classi	fication code:	M11		Tunnel restriction cod	le: E
Limite	d Quantity:	acc. AD	DR 3.3	.1/251: see LQ in Alteri	native declaration for transportation
Air tra	nsport				
PAX:		960		max. weight PAX:	10 KG
CAO:		960		max. weight CAO:	10 KG
	ne transport				
EmS:		F-A, S-	Р	Storage category:	A

Or use Alternative declaration for transportation:



Tel.:

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: US: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058	NANOCOLOR Manganese 10	Page: 10/11
Printing date: 01.10.2019	Date of issue: 13.08.2019	

UN No.: (see below) class 8 II, Excepted Quantities (≤30 mL/∑≤500 mL) = ADR/ IATA E2 or

14.1 UN number: 3266 14.2 UN proper shipping name: Corrosive liquid, basic, inorganic, n.o.s. (ammonia solution) 14.3 Class: 14.4 Packing group: 8 Road transport C5 Classification code: Tunnel restriction code: Е Limited Quantity: 1 L Excepted Quantity: E 2 Air transport PAX: 851 max. weight PAX: 1 L CAO: 855 max. weight CAO: 30 L Maritime transport F-A, S-B EmS: Storage category: В

14.5 **Environmental hazards**

none, contains only small quantities of hazardous substances

14.6 Special precautions for user

not necessary

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013 German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung -GefStoffV), revised on November 2010, according to Directive 98/24/EC TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011

MN Leaflet/User manual, also see www.mn-net.com Look for your country-specific regulations.

15.2 **Chemical safety assessment**

not necessary for these small amounts ---

SECTION 16: Other information

List of H and P phrases 16.1

16.1.1	List of relevant H phrases					
	H290	May be corrosive to metals.				
	H302	Harmful if swallowed.				
	H312	Harmful in contact with skin.				
	H314	Causes severe skin burns and eye damage.				
	H317	May cause an allergic skin reaction.				
	H335	May cause respiratory irritation.				
	H351	Suspected of causing cancer.				
	H373	May cause damage to organs through prolonged or repeated exposure.				
16.1.2	List of relevant P phrases					
	P201	Obtain special instructions before use.				
	P260sh	Do not breathe dust/vapours.				
	P261sh	Avoid breathing dust/vapours.				
	P264W	Wash with water thoroughly after handling.				
	P280sh	Wear protective gloves/eye protection.				
	P301+312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.				
	P302+352	IF ON SKIN: Wash with plenty of water.				
	P303+361+353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].				
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to				
		do. Continue rinsing.				
	P310	Immediately call a POISON CENTER/doctor.				
	P330	Rinse mouth.				



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: US: Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272 Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985058 NANOCOLOR Manganese 10 Page: 11/1' Printing date: 01.10.2019 Date of issue: 13.08.2019

P390 P403+233 Absorb spillage to prevent material damage

Store in a well-ventilated place. Keep container tightly closed.

16.2 Training advice

Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products

16.3 Recommended restriction on use

Only for professional user.

Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)! Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EEC or for DE §§ 11-13 MuSchG 2017)! An individual package of this product or test kit has a moderate hazardous potential.

16.4 Further information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

16.5 Sources of key data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS

Regulation 487/2013/EU, 4th adaptation of CLP regulation to technical and scientific progress Regulation 669/2018/EU, 4th adaptation of CLP regulation to technical and scientific progress

TRGS 900, German engineering rules governing limits in air at work, updated 03/2018 SUVA .CH, Limits in air at work 2009, revised on 01.2009

TRGS 907, German engineering rules governing listing of substances and causes of sensitizations, updated November 2011 KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

Revisions/Updates

Reason for Revision: 2016-03 Adaptation of regulation 1221/2015/EU

