

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR total Nitrogen TNb 22 Page: 1/14

Printing date: 01.10.2019 Date of issue: 20.05.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 **Product identifier**

REF 985083

Product name NANOCOLOR total Nitrogen TNb 22

REACH Registration number(s): see SECTION 3.1/3.2 or
A registration number for the substance(s) does not exist because the annual tonnage does not require registration or

the substance or its use is excluded from registration.

1 x 20x 14 mg NANOFIX Compensation reagent

1 x 11 mL NO<sub>3</sub> /N (R2)

20 x 4 mL total Nitrogen TNb 22 (R0)

20 x 0,18 g Decomposition tube TN<sub>b</sub> 22 (RA)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

### Relevant identified uses

Product for analytical use.

Exposure Scenario Classification according REACh, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0

The exposure scenario is integrated into sections 1-16.

not described

#### 1.3 Details of the supplier of the safety data sheet

### Manufactured by:

MACHEREY-NAGEL GmbH & Co. KG

Neumann-Neander-Str. 6-8, 52355 Dueren, GERMANY

Tel.: +49 2421 969 0 E-mail: sds@mn-net.com (msds@mn-net.com)

#### 1.4 **Emergency telephone number**

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service. 99089 Erfurt tel. +49 361 730 730 DE: Gemeinsames Giftinformationszentrum (GGIZ)

You find our current versions of SDS (22 languages) in Internet:

http://www.mn-net.com/SDS

## **SECTION 2: Hazard identification**

### Classification of the complete product 2.0



GHS02



GHS03



GHS05





GHS08

US:

Signal word **DANGER** 

Hazard identification	Hazard classes/categories
H226	Flam. Liq. 3
H272	Ox. Sol. 2
H290	Met. Corr. 1
H302	Acute Tox. 4 oral
H314	Skin Corr. 1B
H315	Skin Irrit. 2
H317	Skin Sens. 1
H319	Eye Irrit. 2
H334	Resp. Sens. 1
H336. H335	STOT SE 3

### 2.1 Classification of the substance or mixture

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:



## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 2/14

Printing date: 01.10.2019 Date of issue: 20.05.2019

## 20x 14 mg NANOFIX Compensation reagent

Do not need labelling as hazardous

Signal word

No hazard class

11 mL NO<sub>3</sub> /N (R2)





Signal word WARNING

**Hazard identification** Hazard classes/categories

H226 Flam. Liq. 3 Eye Irrit. 2 H319 H336, H335 STOT SE 3

### 4 mL total Nitrogen TNb 22 (R0)





GHS07

**DANGER** Signal word

Hazard identification	Hazard classes/categories	
H290	Met. Corr. 1	
H302	Acute Tox. 4 oral	
H314	Skin Corr. 1B	

### 0,18 g Decomposition tube TN<sub>b</sub> 22 (RA)







Signal word **DANGER** 

Hazard identification	Hazard classes/categories
H272	Ox. Sol. 2
H302	Acute Tox. 4 oral
H315	Skin Irrit. 2
H317	Skin Sens. 1
H319	Eye Irrit. 2
H334	Resp. Sens. 1
H335	STOT SF 3

#### 2.2 Label elements

According CLP directive inner packages must be only labelled with GHS symbol(s) and product identificator(s) (EU 1272/2008 Annex I - 1.5.1.2). Inner packages up to 10 mL need max. 2 symbols (Annex I - 1.5.2.4.1 / 2).

Harmful chemicals/mixtures with signal word: WARNING and highly flammable chemicals/mixtures must not be labelled with H and P phrases until 125 mL (EU 1272/2008 Annex I - 1.5.2). This labelling exemption is NOT valid for sensibilizing substances. Oxidizing mixtures with signal word: **DANGER** and **H272** must not be labelled with H and P phrases until 125 mL. Metal corrosive solutions do not have to be labelled with GHS symbol, signal word, H and P phrases until 125 mL (EU 1272/2008 Annex I - 1.5.2.1.3).

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

+49 24 21 969-0 Tel.: +41 62 388 55 00 +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272

Version: M V 4.10.1 E-mail: info@mn-net.com

E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com

## **ACHEREY-NAGE**I



## Safety Data Sheet

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 3/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

## 20x 14 mg NANOFIX Compensation reagent

Do not need labelling as hazardous Signal word: -

## 11 mL NO<sub>3</sub> /N (R2)





Signal word: WARNING

### 4 mL total Nitrogen TNb 22 (R0)





Signal word: DANGER

H314

Causes severe skin burns and eye damage.

P260sh, P280sh, P303+361+353, P305+351+338, P310

Do not breathe dust/vapours. Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

### 0,18 g Decomposition tube TN<sub>b</sub> 22 (RA)







GHS03

GHS07

GHS08

Signal word: DANGER

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

P261sh, P280sh, P342+311

Avoid breathing dust/vapours. Wear protective gloves/eye protection. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

#### 2.3 Other hazards

### Possible hazards from physicochemical properties

Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive. In the case of pH values are less than 5 or higher than 9 then it is irritant. Flammable properties.

### Information pertaining to particular risks to human and possible symptoms

Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs.

Cause after oral intake, inhalation of vapours/dust, skin contact, impairments of health when ingested in small quantities. May cause sensitization by skin contact, also in repeated contact of small amounts. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Information pertaining to particular risks to the environment

Avoid contact of substance/mixture to environment.

PRTnot applicable vPvB: not applicable

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Fax: Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com

E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com



## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 4/14 Date of issue: 20.05.2019 Printing date: 01.10.2019

Other hazards

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances or 3.2 Mixtures

20x 14 mg NANOFIX Compensation reagent

Chemical: CAS No.: 7757-83-7 sodium sulfite

Classification: No criteria for classification or naming of chemical not required.

Na<sub>2</sub> SO<sub>3</sub>, E221 Formula:

Pseudonym: sulfurous acid, disodium salt

TSCA Inventory: listed

REACH Reg. No.: 01-2119537420-49-xxxx

EC No.: 231-821-4 WE2150000 RTECS: KE-31612 KF No . 70 - <100 % Concentration:

acc. CLP (GHS): The criteria for classification are not fulfilled

11 mL NO<sub>3</sub>/N (R2)

Chemical: 2,6-dimethylphenol CAS No.: 576-26-1

Classification: H301, Acute Tox. 3 oral, H311, Acute Tox. 3 derm., H314, Skin Corr. 1B, H411, Aquatic Chronic 2

Formula: C<sub>8</sub> H<sub>10</sub> O; (CH<sub>3</sub>)<sub>2</sub> -C<sub>6</sub> H<sub>3</sub> -OH

Pseudonym: 2,6-xylenol

TSCA Inventory: listed

REACH Reg. No.: 01-2119552794-29-xxxx

EC No.: 209-400-1 Indice No.: 604-006-00-X RTECS: ZE6125000 MFCD: 00002240

KF No . KE-35435, >5% Toxic 97-1-274

Concentration: 0.1 - <1 %

acc. CLP (GHS): The criteria for classification are not fulfilled.

Chemical: CAS No.: 67-63-0 2-propanol

Classification: H225, Flam. Liq. 2, H319, Eye Irrit. 2, H336, STOT SE 3

Formula: C<sub>3</sub> H<sub>8</sub> O

Pseudonym: isopropanol, IPA, propan-2-ol

TSCA Inventory: listed

REACH Reg. No.: 01-2119457558-25-XXXX

603-117-00-0 EC No.: 200-661-7 Indice No.: NT8050000 RTFCS: MFCD: 00011674

KE No.: KE-29363 Concentration: 35 - < 50 %

acc. CLP (GHS): H226, Flam. Liq. 3, H319, Eye Irrit. 2, H336, STOT SE 3

4 mL total Nitrogen TN<sub>b</sub> 22 (R0)

o-phosphoric acid Chemical: CAS No.: 7664-38-2

Classification: H290, Met. Corr. 1, H302, Acute Tox. 4 oral, H314, Skin Corr. 1B

Formula: H<sub>3</sub> PO<sub>4</sub> •H<sub>2</sub> O Pseudonym: orthophosphoric acid

TSCA Inventory: listed

REACH Reg. No.: 01-2119485924-24-xxxx

EC No.: 231-633-2 Indice No.: 015-011-00-6

RTECS: TB6300000 KE No.: KE-27427 Concentration: 25 - <40 %

acc. CLP (GHS): H290, Met. Corr. 1, H302, Acute Tox. 4 oral, H314, Skin Corr. 1B

www.mn-net.com

US:

MACHEREY-NAGE **(MN)** 

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:



## Safety Data Sheet

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 5/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

> Chemical: sulfuric acid CAS No.: 7664-93-9

H314. Skin Corr. 1B Classification: Formula: H<sub>2</sub> SO<sub>4</sub> (•H<sub>2</sub> O)

TSCA Inventory: listed

REACH Reg. No.: 01-2119458838-20-xxxx

EC No.: 231-639-5 Indice No.: 016-020-00-8

WS5600000 RTFCS KE-32570, >10% Toxic 97-1-405, Acc. Precaution Chem. KE No .:

51 - <65 %

Concentration: acc. CLP (GHS): H314, Skin Corr. 1B

0,18 g Decomposition tube TN<sub>b</sub> 22 (RA)

Chemical: sodium carbonate CAS No.: 497-19-8

Classification: H319, Eye Irrit. 2 Formula: Na<sub>2</sub> CO<sub>3</sub>

TSCA Inventory: listed

REACH Reg. No.: 01-2119485498-19-xxxx

EC No.: 207-838-8 011-005-00-2 Indice No.:

RTECS: VZ4050000 KE-31380 KF No . Concentration: 20 - < 50 % acc. CLP (GHS): H319, Eye Irrit. 2

potassium peroxydisulfate Chemical: CAS No.: 7727-21-1

Classification: H272, Ox. Liq. 2, H302, Acute Tox. 4 oral, H315, Skin Irrit. 2, H317, Skin Sens. 1, H319, Eye Irrit. 2, H334, Resp. Sens. 1, H335, STOT SE 3

Formula: K<sub>2</sub> O<sub>8</sub> S<sub>2</sub> Pseudonym: potassium persulfate

TSCA Inventory:

REACH Reg. No.: 01-2119495676-19-xxxx

231-781-8 FC No : 016-061-00-1 Indice No : RTECS: SE0400000 MFCD: 00011386

KE No.: KE-12177 Concentration: 60 - <80 %

acc. CLP (GHS): H272, Ox. Liq. 2, H302, Acute Tox. 4 oral, H315, Skin Irrit. 2, H317, Skin Sens. 1, H319, Eye Irrit. 2,

H334, Resp. Sens. 1, H335, STOT SE 3

#### 3.3 Remarks

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%.

List of H and P phrases: see section 16.1

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor. Take to a doctor, in a raised position if there are breathing difficulties.

## 4.1.1

Remove contaminated clothing immediately. Rinse the affected skin or mucous membrane thoroughly for min. 15 minutes under running water. (If possible) use soap. Avoid neutralisation. Then apply a loose bandage.

### 4.1.2

After contact with the eyes rinse thoroughly under running water with the eyelid wide open for min. 10 minutes with eye washing bottle, eye douche or running water (protect intact eye). Before (if possible) apply eye drops Proxymetacaine 0.5%, if the opening the eyelid convulsion is painful. Further treatment to be carried out by an eye specialist.

#### 4.1.3 After INHALATION of vapours

After inhalation of foam or vapour fresh air should be inhaled. Keep airways free. If vomiting and if insensible place patient in recovery position and keep airways free. Administer a Dexamethasone spray as soon as possible. Ensure quiet, warmth, and provide resuscitation if necessary. In the event of respiratory distress ensure that the patient inhales oxygen. Secure the breathing, heart and circulatory function. ---

## 4.1.4

After oral intake lots of water with activated charcoal supplement should be drunk after it has been ingested. Do not induce vomiting under any circumstances. Do not make any efforts to neutralise it. Contact medical advice for possible consequences. ---

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR: US:



## **Safety Data Sheet**

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 6/14
Printing date: 01.10.2019 Date of issue: 20.05.2019

## 4.2 Most important symptoms and effects, both acute and delayed

Chronic Effects: May cause sensitization by skin contact, also in repeated contact of small amounts. May cause allergy or asthma symptoms or breathing difficulties if inhaled. ---

### 4.3 Indication of any immediate medical attention and special treatment needed

CORROSIVE DAMAGE: After SKIN CONTACT rinse with water for a long time. Efforts to neutralise the substance can frequently make matters worse. Apply glucocorticosteroides following inflammatory reactions. After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must to be carried out by an eye specialist. After INTAKE administer aluminium oxide drug suspensions. Administer a prophylaxis to counter pulmonary oedema following the INGESTION of corrosive aerosols. In the event of RESPIRATORY DISTREES ensure that the patient inhales oxygen. Inform patient respectively further measures and the possibility of long-term damages. ---

## SECTION 5: Firefighting measures

## 5.1 Extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

## 5.2 Special hazards arising from the substance or mixture

WARNING: Flammable (GHS regulation). May form explosive vapour-air mixtures. Formation of hazardous and caustic vapour-air mixtures possible. ---

## 5.3 Advice for firefighters

No, for listed product. Product package burns like paper or plastic. Spray any vapours released with water. Retent fire water. Use only acid-resistant safety equipment.

For great amount - if necessary - protective breathing apparatus which is independent of the ambient air (isolated equipment), and sealed protective clothing is necessary in the event of a large-scale formation of toxic substances.

### 5.4 Additional information

Danger for environment only in the event of a large-scale leakage or formation of hazardous substances. ---

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapours. Wear suitable protective gloves (see 8.2.2). Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.

## 6.2 Environmental precautions

not necessary

## 6.3 Methods and material for containment and cleaning up

Bind any escaping liquid with inert absorbent. And dispose in accordance to local regulations for the disposal of hazardous chemicals. Clean any contaminated equipment and floors with plenty of water.

Collect small amounts of leaked liquid and flush with water into drains.

### 6.4 Reference to other sections

see information in section 5.4 ---

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Handling in accordance with the test instruction, that comes with the product. Use only in well-ventilated working areas. Use a safety bottle when shaking test tubes.

## 7.2 Conditions for safe storage, including any incompatibilities

The original product package of MACHEREY-NAGEL allows a safe storage.

Storage class (VCI): Water hazard class (DE):

## 7.2.1 Requirements for stock rooms and containers

Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of glass bottles.

## 7.3 Specific end use(s)

Product for analytical use.

www.mn-net.com

US:

ISO 9001 CERTIFIED MACHEREY-NAGEL GmbH & Co. KG  $\cdot$  Neumann-Neander-Str. 6–8  $\cdot$  52355 Düren  $\cdot$  Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Fax: Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com

E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com



## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR total Nitrogen TNb 22 Page: 7/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

20x 14 mg NANOFIX Compensation reagent

Chemical: sodium sulfite CAS No.: 7757-83-7

298<sub>inh</sub> mg/m<sup>3</sup> DNEL = Derived No-Effect Level (for workers)

TRGS 900 (DE):

11 mL NO<sub>3</sub>/N (R2)

Chemical: 2,6-dimethylphenol CAS No.: 576-26-1

not listed ppm

[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

not listed ppm OSHA:

Chemical: 2-propanol CAS No.: 67-63-0

DNEL: [inh] 500 mg/m<sup>3</sup> DNEL = Derived No-Effect Level (for workers) PNEC (fresh water): 140.9 mg/L PNEC = Predicted No Effected Concentration

TRGS 900 (DE): 200 ppm / 500 mg/m<sup>3</sup>

Short-term exposure factor: 2 (II), Y

skin resorptive (H), respiratory sénsitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 200 ppm / 500 mg/m<sup>3</sup> TRGS 903 (DE):

[Aceton B/b, U/b] 25 mg/L B blood, U urine, a no limitation, b end of exposition or shift

[TWA] 400 ppm / 980 mg/m<sup>3</sup>

NIOSH STEL: 500 ppm / 1225 mg/m³ [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 400 ppm / 980 mg/m<sup>3</sup>

4 mL total Nitrogen TNb 22 (R0)

CAS No.: 7664-38-2 Chemical: o-phosphoric acid

DNEL: 2.92 mg/m<sup>3</sup> DNEL = Derived No-Effect Level (for workers)

EU value: [TWA] 1 /[STEL] 2 mg/m<sup>3</sup> [8h] 1 / [15min] 2 mg/m<sup>3</sup> TRGS 900 (DE):

Short-term exposure factor: 2 (I), Y

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 1 mg/m<sup>3</sup>

TWA 1 / ST 3 mg/m<sup>3</sup> NIOSH:

NIOSH STEL: 3 mg/m³ [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: TWA 1 mg/m<sup>3</sup>

Chemical: sulfuric acid CAS No.: 7664-93-9

[inh] 50 µg/m³ Level (for workers) DNEL: DNEL = Derived No-Effect PNEC (fresh water): 2.5 µg/L PNEC = Predicted No Effected Concentration 0.1 e mg/m<sup>3</sup> EU value:

TRGS 900 (DE): 0.1 E mg/m<sup>3</sup> Short-term exposure factor:

skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value:

NIOSH: NTP Report on Carcinogens (RoC) List Yes (Known to be a human carcinogen); [TWA] 1 mg/m<sup>3</sup> [TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA:

0,18 g Decomposition tube TNb 22 (RA)

www.mn-net.com



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 +41 62 388 55 05 +33 388 51 76 88 +1 484 821 1272 Fax: Fax: Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com

E-mail: sales-us@mn-net.com



## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 8/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

> Chemical: CAS No.: 497-19-8 sodium carbonate

 $\frac{10_{inh}\ mg/m^3}{\text{DNEL} = \text{Derived No-Effect Level (for workers)}}$ DNEL:

TRGS 900 (DE):

E/e respirable

CAS No.: 7727-21-1 Chemical: potassium peroxydisulfate

[derm] 18,2 mg/kg bw/day; [inh] 2.06 mg/m<sup>3</sup> DNEL:

Level (for workers) TRGS 900 (DE):

E/e respirable NIOSH: not listed

[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: not listed

#### 8.2 **Exposure controls**

Good ventilation and extraction system in the room, floor resistant to chemicals with floor drainage and washing facilities. The highest level of cleanliness must be maintained at the workplace.

#### 8.2.1 Respiratory protection

Use for open access of these substances for example a protection filter, class A/AX. No additional recommendations.

### 8.2.2

Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

### 8.2.3

Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.

## 8.2.4

Recommended to avoid clothing damage, and to avoid contamination with these hazards.

### 8.2.5

Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

### 20x 14 mg NANOFIX Compensation reagent

Appearance: solid (lyoph.) Odor: odorless

11 mL NO<sub>3</sub> /N (R2)

Appearance: liquid Colour: rose Odor: alcoholic

pH: Flash point: 6-8 18.5 °C Specific gravity: 0,9 g/cm<sup>3</sup> Solubility in water: 0-100 %

4 mL total Nitrogen TNb 22 (R0)

Appearance: liquid Colour: colourless Odor: odorless

0-1 pH: Specific gravity: 1,79 g/cm<sup>3</sup> Solubility in water: 0-100 %

0,18 g Decomposition tube TNb 22 (RA)

Colour: colourless Appearance: solid Odor: odorless

5-7 Solubility in water: 0-30 %

#### 9.2 Other information

Data for the other parameters of the mixtures are not available, because no registration and no chemical safety report is required. **Relevant Properties of Substance Group** 

www.mn-net.com

US:

MACHEREY-NAGE (MN)

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:



## Safety Data Sheet

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 9/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

## **SECTION 10: Stability and reactivity**

10.1 Reactivity

Strong CORROSIVE, no further data available.

10.2 Chemical stability

No known instability.

10.3 Possibility of hazardous reactions

Can react violently with organic material. No further data available.

10.4 Conditions to avoid

Not necessary. Observe labeled storage temperature. ---

10.5 Incompatible materials

Avoid contact with strong acids or alkalines.

10.6 Hazardous decomposition products

> In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions.

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Following information is valid for pure substances. Quantitative data on the toxicity of this product are not available.

### 20x 14 mg NANOFIX Compensation reagent

Chemical: sodium sulfite CAS No.: 7757-83-7

TSCA Inventory: listed Korea Exist.Chem.Inventory: KE-31612 2610 mg/kg LD50<sub>orl rat</sub>: LC50ihl rat: >5.54h mg/L

11 mL NO<sub>3</sub> /N (R2)

Chemical: 2,6-dimethylphenol CAS No.: 576-26-1

TSCA Inventory: listed California Proposition 65 List: not listed

Target Organs: Leber, Niere

Australia NICNAS: not listed Canada CEPA 1999: DSL yes

Japan CSCL/PRTR: PRTR - Class I Designated Chemical Substance Yes, Japan PDSCL: not listed

not listed Japan ISHL: South Korea TCCA: not listed

Korea Exist.Chem.Inventory: KE-35435, >5% Toxic 97-1-274

LD50<sub>orl rat</sub>: 296 mg/kg LC\_Lowihl rbt: 500 mg/m<sup>3</sup> LD50<sub>drm rat</sub>: 2325 mg/kg LD50<sub>drm rbt</sub>: 1000 mg/kg LD50<sub>orl mus</sub>: 450 mg/kg

Chemical: CAS No.: 67-63-0 2-propanol

TSCA Inventory: California Proposition 65 List: not listed listed

ACGIH: 1230 ppm

inhalation, ingestion, skin and/or eye contact **Exposure Routes:** 

Target Organs: Eyes, skin, respiratory system

Symptoms: irritation eyes, nose, throat; drowsiness, dizziness, headache; dry cracking skin; in animals: narcosis

Australia NICNAS: Canada CEPA 1999: DSL yes

Japan CSCL/PRTR: PAC yes, Japan PDSCL: -

Japan ISHL: listed ≥1,0%/≥0,1%, Article 57-2 (SDS required)

South Korea TCCA:

Korea Exist.Chem.Inventory: KE-29363 5045 mg/kg LD50<sub>orl rat</sub>: 3570 mg/kg LC Loworl hmn: LC50<sub>ihl rat</sub>: 164h g/m3 LD50<sub>drm rbt</sub>: 12.8 g/kg

TRGS 905 (DE): R<sub>F</sub> C

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:



## Safety Data Sheet

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 10/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

4 mL total Nitrogen TNb 22 (R0)

o-phosphoric acid Chemical: CAS No.: 7664-38-2

TSCA Inventory: listed California Proposition 65 List: not listed

ACGIH: 1 ppm

**Exposure Routes:** inhalation, ingestion, skin and/or eye contact

Target Organs: Eyes, skin, respiratory system

Symptoms: irritation eyes, skin, upper respiratory system; eye, skin, burns; dermatitis

Australia NICNAS: not listed Canada CEPA 1999: DSL Yes

Japan CSCL/PRTR: not listed, Japan PDSCL: not listed

Japan ISHL: listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)

South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-27427 LD50<sub>orl rat</sub>: 1530 mg/kg LC50<sub>ihl rbt</sub>: 1.689 mg/L LD50<sub>drm rbt</sub>: 2750 mg/kg

Acute Effects: Cause after oral intake, impairments of health when ingested in small quantities.

TRGS 905 (DE): R<sub>F</sub> C

CAS No.: 7664-93-9 Chemical: sulfuric acid

TSCA Inventory: listed California Proposition 65 List: not listed

ACGIH: 1 ppm

**Exposure Routes:** inhalation, ingestion, skin and/or eye contact Target Organs: Eyes, skin, respiratory system, teeth

Symptoms: irritation eyes, skin, nose, throat; pulmonary edema, bronchitis; emphysema; conjunctivitis; stomatis;

dental erosion; eye, skin burns; dermatitis

Australia NICNAS: not listed Canada CEPA 1999: DSL Yes

Japan CSCL/PRTR: not listed, Japan PDSCL: Deleterious Substance Japan ISHL: listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)

South Korea TCCA: Accident Precaution Chemical Yes

Korea Exist.Chem.Inventory: KE-32570, >10% Toxic 97-1-405, Acc. Precaution Chem.

LD50<sub>orl rat</sub>: 2140 mg/kg

LC50ihl rat: [8h] 600/ [4h] 850 mg/m<sup>3</sup>

TRGS 905 (DE):

0,18 g Decomposition tube TNb 22 (RA)

Chemical: sodium carbonate CAS No.: 497-19-8

TSCA Inventory: listed Korea Exist.Chem.Inventory: KE-31380 LD50<sub>orl rat</sub>: 4090 mg/kg LC Loworl rat: 4000 mg/kg LC50<sub>ihl rat</sub>: 2300<sub>2h</sub> mg/m<sup>3</sup>

Chemical: potassium peroxydisulfate CAS No.: 7727-21-1

TSCA Inventory: listed California Proposition 65 List: not listed Australia NICNAS: Yes (PEC/18) Canada CEPA 1999: DSI Yes

not listed, Japan PDSCL: not listed Japan CSCL/PRTR:

Japan ISHL: listed ≥1,0%/≥0,1%, Article 57-2 (SDS required)

South Korea TCCA: not listed Korea Exist.Chem.Inventory: KE-12177

LD50<sub>orl rat</sub>: 802 mg/kg
Acute Effects: Cause after oral intake, inhalation of vapours/dust, skin contact, impairments of health when ingested in small

Chronic Effects: May cause sensitization by skin contact, also in repeated contact of small amounts. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

TRGS 907 (DE): Sah

## **SECTION 12: Ecological information**

#### 12.1 **Toxicity**

Following information is valid for pure substances.

20x 14 mg NANOFIX Compensation reagent

www.mn-net.com

MACHEREY-NAGE <MN>

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com

E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

## **ACHEREY-NAGEI**



## **Safety Data Sheet**

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 11/14

Date of issue: 20.05.2019 Printing date: 01.10.2019

> Chemical: sodium sulfite CAS No.: 7757-83-7

LC50<sub>fish/96h</sub>: 315<sub>96h</sub> mg/L EC10<sub>pseudomonas putita/16h</sub>: 260<sub>17h</sub> mg/L

Water hazard class (DE): WGK No.: 0282

Dispersion coefficient(octanol-water) Storage class (VCI): 12-13

11 mL NO<sub>3</sub> /N (R2)

2.6-dimethylphenol Chemical: CAS No.: 576-26-1

 $LC50_{\mbox{\footnotesize pimephales}}$  promelas/96h : 22-27 mg/L EC50<sub>daphnia/48h</sub>: 11.2 mg/L

Water hazard class (DE): WGK No.: 1689

Dispersion coefficient(octanol-water) 2.36 Storage class (VCI): 6 1 C

Chemical: 2-propanol CAS No.: 67-63-0

PNEC (fresh water):
PNEC = Predicted No Effected Concentration 140.9 mg/L

LC50<sub>fish/96h</sub>: 1400 mg/L EC50<sub>daphnia/48h</sub>: 13.3 g/L IC50scenedesmus quadricauda/72h: >1000 mg/L EC10<sub>pseudomonas putita/16h</sub> EC5: 1050 mg/L Water hazard class (DE): WGK No.: 0135

Dispersion coefficient<sub>(octanol-water)</sub>: 0.05 Storage class (VCI):

4 mL total Nitrogen TN<sub>b</sub> 22 (R0)

o-phosphoric acid CAS No.: 7664-38-2 Chemical:

Avoid contact of substance/mixture to environment. LC50<sub>fish/96h</sub>: 3-3.5 mg/L

Water hazard class (DE): WGK No.: 0392

Storage class (VCI): 8 B

CAS No.: 7664-93-9 sulfuric acid Chemical:

Avoid contact of substance/mixture to environment. PNEC<sub>(fresh water)</sub>:
PNEC = Predicted No Effected Concentration 2.5 µg/L

LC50<sub>fish/96h</sub>: [NOEC, 65d] 25 µg/L EC50daphnia/48h: 100 mg/L EC10<sub>pseudomonas putita/16h</sub>: [72h] 100 mg/L

Water hazard class (DE): WGK No.: 0182

Storage class (VCI):

0,18 g Decomposition tube  $TN_b$  22 (RA)

CAS No.: 497-19-8 Chemical: sodium carbonate

LC50<sub>fish/96h</sub>: 300 ma/L EC50<sub>daphnia/48h</sub>: 265 mg/L

Water hazard class (DE): WGK No.: 0222

Storage class (VCI):

potassium peroxydisulfate CAS No.: 7727-21-1 Chemical:

Water hazard class (DE): WGK No.: 1350

Storage class (VCI): 5.1 B

12.2 Persistence and degradability

not necessary

12.3 Bioaccumulative potential

not necessary

12.4 Mobility in soil

not necessary

12.5 Results of PBT and vPvB assessment

no data available

www.mn-net.com

US:

MACHEREY-NAGE **(MN)** 

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:



## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR total Nitrogen TNb 22 Page: 12/14 Printing date: 01.10.2019 Date of issue: 20.05.2019

#### 12.6 Other adverse effects

no additional data available

## **SECTION 13: Disposal considerations**

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

#### 13.1 Waste treatment methods

## **SECTION 14: Transport information**

14.1. UN number: 3316 14.2. UN proper shipping name: Chemical Kit 14.3. Class: 14.4. Packing group: Road transport Classification code: M11 Tunnel restriction code: Limited Quantity: acc. ADR 3.3.1/251: see LQ in Alternative declaration for transportation Air transport PAX: 960 max. weight PAX: 10 KG 960 CAO: max. weight CAO: 10 KG Maritime transport F-A, S-P EmS: Storage category: Α Or use Alternative declaration for transportation: UN No.: (see below) class 5.1 III, Excepted Quantities (≤30 mL/∑≤1 L) = ADR/ IATA E1 UN 1993 class 3 II, class 8 II, Excepted Quantities (≤30 mL/∑≤500 mL) = ADR/ IATA E2 or 14.1 UN number: 14.2 UN proper shipping name: Flammable liquid, n.o.s. (2-propanol mixture) 14.3 Class: 14.4 Packing group: II Road transport Classification code: F1 Limited Quantity: 1 I Tunnel restriction code: Ε **Excepted Quantity:** E 2 Special instructions: 640C Air transport PAX: 353 max. weight PAX: 5 L CAO: 364 max. weight CAO: 60 L Maritime transport EmS: F-E, S-E Storage category: В 14.1 UN number: 3215 14.2 UN proper shipping name: Persulphates, inorganic, n.o.s. 14.3 Class: 14.4 Packing group: III 5.1 Road transport Classification code: 02 Limited Quantity: 5 Kg Tunnel restriction code: F **Excepted Quantity:** F 1 Air transport PAX: 559 max. weight PAX: 25 Kg CAO: 563 max. weight CAO: 100 Kg Maritime transport F-A, S-Q Storage category: Maritime pollutant (5.2.1.6): (Limited Quantity (LQ) until 5 L|kg per inner package) 14.1 UN number: 3264 14.2 UN proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (o-phosphoric acid, sulfuric acid solution) 14.3 Class: 14.4 Packing group: Road transport Classification code: C1 Tunnel restriction code: F Limited Quantity: 1 I **Excepted Quantity:** E 2 Air transport PAX: max. weight PAX: CAO: 855 max. weight CAO: 30 L Maritime transport F-A, S-B EmS: Storage category: В

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 +41 62 388 55 05 +33 388 51 76 88 +1 484 821 1272 Fax: Fax: Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

REF: 985083 NANOCOLOR total Nitrogen TNb 22 Page: 13/14 Printing date: 01.10.2019 Date of issue: 20.05.2019

#### 14.5 **Environmental hazards**

none, contains only small quantities of hazardous substances

#### 14.6 Special precautions for user

not necessary

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013 German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung -GefStoffV), revised on November 2010, according to Directive 98/24/EC

TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011

MN Leaflet/User manual, also see www.mn-net.com

Look for your country-specific regulations.

#### 15.2 Chemical safety assessment

not necessary for these small amounts ---

### **SECTION 16: Other information**

### 16.1 List of H and P phrases

#### 16.1.1 List of relevant H phrases

H226	Flammable liquid and vapour.
H272	May intensify fire; oxidizer.
H290	May be corrosive to metals.
H302	Harmful if swallowed

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

List of relevant P phrases 16.1.2

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260D Do not breathe vapours. P260sh Do not breathe dust/vapours. P261sh Avoid breathing dust/vapours.

P264W Wash with water thoroughly after handling. P280sh Wear protective gloves/eye protection.

P301+312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.
Immediately call a POISON CENTER/doctor. P310

P330

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P390 Absorb spillage to prevent material damage.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

#### 16.2 Training advice

Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products.

### 16.3 Recommended restriction on use

Only for professional user.

Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)!

Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EÉC or for DE §§ 11-13 MuSchG 2017)!

An individual package of this product or test kit has a moderate hazardous potential.

www.mn-net.com

US:

MACHEREY-NAGE (MN)

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984 Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 +1 484 821 1272 Fax:

Version: M V 4.10.1 E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com



# **Safety Data Sheet**

## according to Regulations 1907/2006/EC (REACh) and 2015/830/EU

NANOCOLOR total Nitrogen TNb 22 Page: 14/14

Printing date: 01.10.2019 Date of issue: 20.05.2019

#### 16.4 **Further information**

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

### 16.5 Sources of key data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS Regulation 487/2013/EU, 4th adaptation of CLP regulation to technical and scientific progress Regulation 669/2018/EU, 4th adaptation of CLP regulation to technical and scientific progress TRGS 900, German engineering rules governing limits in air at work, updated 03/2018 SUVA .CH, Limits in air at work 2009, revised on 01.2009

TRGS 907, German engineering rules governing listing of substances and causes of sensitizations, updated November 2011 KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

### Revisions/Updates

Reason for Revision: 2016-03 Adaptation of regulation 1221/2015/EU

www.mn-net.com

MN>

MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · 52355 Düren · Germany DE/international: CH: FR: